

Engen Primax Unleaded with Pro-Drive

Description

Engen Primax Unleaded with Pro-Drive Unleaded petrols (ULP) are blended in South Africa for optimum performance under harsh South African conditions, and are available in two grades:

- 95 Octane for use at altitudes below 1200 meters
- 93 Octane for use at altitudes above and including 1200 meters

Engen Primax Unleaded with Pro-Drive 95 is available at selected Inland retail service stations to enable high performance vehicles to utilise the benefits from a higher-octane petrol.

Engen Primax Unleaded exhibits excellent oxidation stability and is formulated with additive fuel technology to clean-up and keep fuel systems clean, restore power and reduce exhaust emissions. Engen Primax Unleaded with Pro-Drive exceeds the latest South African National Standards (SANS 1598) specifications.

Application

Engen Primax Unleaded with Pro-Drive is suitable for service in all spark ignition internal combustion engines making use of fuel injection (including Gasoline Direct Injection) or carburetted systems in motor vehicles, motorcycles, lawn mowers and outboard motors. Engen Primax Unleaded with Pro-Drive is recommended for use in late model, high performance engines designed to run on fuels of this type.

Benefits

- Quick & easy starting; fast warm up; rapid acceleration, freedom from vapour lock
- Outstanding anti-knock resistance
- Cleaner burning resulting in cleaner engines
- Combustion chamber deposit (CCD) control
- Excellent intake manifold, carburettor system and fuel injection component cleanliness
- Maximum engine durability and reliability
- Outstanding lubricant anti-sludge performance
- Enhanced power, acceleration, and reduced fuel consumption
- Smoother running engine
- Direct injection gasoline technology compliant

Typical Physical Characteristics

	Engen Primax Unleaded with Pro-Drive	Engen Primax Unleaded with Pro-Drive
Research Octane Number, min.	93	95
Initial Boiling Point, °C, typ.	34	37
Final Boiling Point, °C, max.	215	215
Colour	Yellow	Green

Performance Level

SANS 1598:2019

Certification Mark – 648/10581

08.2021

Due to continual product research and development, the information contained herein is subject to change without notification. Refer to the Material Safety Data Sheet (MSDS) for information on the safe handling and use of this product.

Engen Petroleum Ltd | Tel: 08600 36436 | Website: www.engenoil.com | Email: 1call@engenoil.com